




Best Electronic Technology Co., Ltd

Office: 5/F, C District, No. 98, Road 9, Pacific Industrial Zone, Xintang Town, Zengcheng District, Guangzhou, China

LED SOLAR FLOOD LIGHT Spec



Wattage	BST-SFL-30W-F01	BST-SFL-50W-F01	BST-SFL-75W-F01	BST-SFL-120W-F01	BST-SFL-200W-F01
Battery	32650 Lifepo4 3.2V/6Ah	32650 Lifepo4 3.2V/12Ah	32650 Lifepo4 3.2V/15Ah	32650 Lifepo4 3.2V/30Ah	32650 Lifepo4 3.2V/40Ah
Chips	64pcs 5730/San'an	100pcs 5730/San'an	150pcs 5730/San'an	240pcs 5730/San'an	400pcs 5730/San'an
Color Temp	6000K-6500K	6000K-6500K	6000K-6500K	6000K-6500K	6000K-6500K
Lumen	4800LM	8000LM	12000LM	19000LM	32000LM
Solar Panel	Polycrystalline 6V/12W	Polycrystalline 6V/18W	Polycrystalline 6V/22W	Polycrystalline 6V/32W	Polycrystalline 6V/40W
Lighting Model	Light Controll+Remote	Light Controll+Remote	Light Controll+Remote	Light Controll+Remote	Light Controll+Remote
Lighting Time	2-3 nights	2-3 nights	2-3 nights	2-3 nights	2-3 nights
Charging Time	4-6 Hrs(If Sunshine)	4-6 Hrs(If Sunshine)	4-6 Hrs(If Sunshine)	4-6 Hrs(If Sunshine)	4-6 Hrs(If Sunshine)
Working Temperature	-10°C ~ +60°C				
Materials	Aluminum Die-Casting+Aluminum Frame Solar Panel				
IP Rating	IP66	IP66	IP66	IP66	IP66
Lamp Size	181*158*50MM	196*172*52MM	240*210*48MM	285*255*57MM	345*310*65MM
Solar Panel Size	350*235*17MM	370*305*17MM	420*350*17MM	600*350*17MM	650*350*17MM
Packing	10 PCS/CTH	8 PCS/CTH	4 PCS/CTH	4 PCS/CTH	4 PCS/CTH
Carton Size	500*390*370MM	550*245*405MM	455*245*400MM	625*265*370MM	695*280*410MM
G.W.	22.5 KGS	22.87 KGS	16.22 KGS	23.05 KGS	28.49 KGS
Warranty	2 Years				

Details:

