

Solar Flood Light C02 CCTV Data Sheet

BST-SFL-150W-C02



BST-SFL-300W-C02



BST-SFL-400W-C02



BST-SFL-400W-C02-4G



Specification

型号	BST-SFL-150W-C02	BST-SFL-300W-C02	BST-SFL-400W-C02	BST-SFL-400W-C02-4G
Light Specification				
Aluminum	Die-cast aluminum			
Dimension	195*171*55mm	240*190*55mm	298*240mm*55mm	298*240mm*55mm
LED chip	Highlight 2835-184PCS	Highlight 2835-304PCS	Highlight 2835-376PCS	Highlight 2835-376PCS
LED chip brand	San an			
Battery capacity	Brand-new lithium battery 15000MAH	Brand-new lithium battery 24000MAH	Brand-new lithium battery 30000MAH	Brand-new lithium battery 42000MAH
Solar panel	Class A Poly Solar Panel 6V 15W (350*350*17MM)	Class A Poly Solar Panel 6V 25W (350*530*17MM)	Class A Poly Solar Panel 6V 30W (350*600*17MM)	Class A Poly Solar Panel 6V 40W (445*670*25MM)
Lumen	855LM	1675LM	1919LM	1919LM
Discharge current	3.2V/1.7A	3.2V/3.2A	3.2V/4.5A	3.2V/4.5A
IP rating	IP67			
Packaging accessories	Waterproof cable/U-shaped frame/remote control/screws/instructions			
CCTV Specification				
Resolution	2 million-1080P			
Lens focal length	4MM			
Recording method	Event recording/24 recording			
Alarm method	APP message push, mobile phone prompt, photo capture			
Power consumption	0.6-0.8W/H			
Intercom method	Two-way intercom			
System	LINUX			
Night vision distance	10-15M			
WIFI Distance	50M without blocking and obstacles			
APP	Tuya Camera			
TF memory card	supports 16-128G			
Storage time	16G-event recording 5-7 days, 24H recording 3-5 days, and so on			